

CONSERVATION UNIT (ROLL-IN)

CONSTRUCTION

- Isothermal doors and panels (105 mm thick) made of heat treated steel and coated with white epoxy
- Injected with polyurethane foam 40 kg /m³
- Door handles fitted on the left unless otherwise specified
- Semi-hermetic compressor for all units of more than 15 m³ and hermetic compressor for all units of less than 15 m³
- Maximum distance of installation : 6 m
- Insulated floor : 145 mm
- Lashes curtain for door 1900 x 950 mm

INSIDE HEIGHT: 2.03 m

Volume of the chamber (in cubic meters)		Depth (in meters)											
		1.2	1.6	2	2.4	2.8	3.2	3.4	4	4.4	4.8	5.2	5.6
Outside width (in meters)	1.2	2.9	3.9	4.9	5.8	6.8	7.8	8.3	9.7	10.7	11.7	12.7	13.6
	1.6	3.9	5.2	6.5	7.8	9.1	10.4	11.0	13.0	14.3	15.6	16.9	18.2
	2	4.9	6.5	8.1	9.7	11.4	13.0	13.8	16.2	17.9	19.5	21.1	22.7
	2.4	5.8	7.8	9.7	11.7	13.6	15.6	16.6	19.5	21.4	23.4	25.3	27.3
	2.8	6.8	9.1	11.4	13.6	15.9	18.2	19.3	22.7	25.0	27.3	29.6	31.8
	3.2	7.8	10.4	13.0	15.6	18.2	20.8	22.1	26.0	28.6	31.2	33.8	36.4
	3.6	8.8	11.7	14.6	17.5	20.5	23.4	24.8	29.2	32.2	35.1	38.0	40.9

INSIDE HEIGHT: 2.43 m

Volume of the chamber (in cubic meters)		Depth (in meters)											
		1.2	1.6	2	2.4	2.8	3.2	3.4	4	4.4	4.8	5.2	5.6
Outside width (in meters)	1.2	3.5	0.0	10.2	0.0	29.8	0.0	86.8	0.0	253.0	0.0	737.7	0.0
	1.6	4.7	6.2	7.8	9.3	10.9	12.4	13.2	15.6	17.1	18.7	20.2	21.8
	2	5.8	7.8	9.7	11.7	13.6	15.6	16.5	19.4	21.4	23.3	25.3	27.2
	2.4	7.0	9.3	11.7	14.0	16.3	18.7	19.8	23.3	25.7	28.0	30.3	32.7
	2.8	8.2	10.9	13.6	16.3	19.1	21.8	23.1	27.2	29.9	32.7	35.4	38.1
	3.2	9.3	12.4	15.6	18.7	21.8	24.9	26.4	31.1	34.2	37.3	40.4	43.5
	3.6	10.5	14.0	17.5	21.0	24.5	28.0	29.7	35.0	38.5	42.0	45.5	49.0